

Bensin pumpeaggregat LH 3



OPERATING CONDITIONS

- Liquid temperature up to 90°C
- Ambient temperature up to 40°C
- Total suction lift up to 7 mt.

MOTOR

- Air cooled single-cylinder gasoline engine
- Electronic ignition
- Silencer and muffler guard for operator protection according to EC norms
- Recoil starter
- Oil level sensor
- Fuel tank capacity 3,6 l

MATERIALS

- Pump body Cast Iron
- Pump support Cast Iron
- Impeller Cast Iron
- Mechanical seal Carbon/Ceramic



APPLICATION

Motor pumps with 4-stroke gasoline engine, particularly suitable for the drainage of slightly dirty waters in the flow irrigation and for the emptying of reservoirs or building excavations, when an electrical connection is not possible.

TECHNICAL DATA

TIPO - TYPE	POTENZA NOMINALE NOMINAL POWER P2	Cilindrata Displacement	Giri r.p.m.	Q = CAPACITY										
				m³/h	6	12	18	24	30	36	42	48	54	60
Motopompa Motor pump				lt/1	100	200	300	400	500	600	700	800	900	1000
4 Tempi - 4 Strokes	HP	cm³		Prevalenza manometrica totale in m.C.A. - Total head in meters w.c.										
LH 3	6,5	196	3200	(m)		20	18	16	14	12	10	5		

BRØDR.
FREBERG AS
Tønsberg